

OUT KIT 21 S

ECG mountings – protection housings



Product family features

- Type of protection: IP67

Product family benefits

- Self-heating: only 5 °C higher than an open ECG

Areas of application

- Outdoor applications in which higher protection against moisture for ECG is needed
- Suitable as additional measure if luminaire does not offer IP67 protection
- Suitable for outdoor installations

Product datasheet

Technical data

Dimensions & weight



Length	455.0 mm
Width	38.0 mm
Height	28.0 mm
Product weight	120.00 g
Mounting hole spacing, length	430.0 mm

Temperatures & operating conditions

Ambient temperature range	-25...+50 °C
---------------------------	--------------

Logistical data

Commodity code	85480090990
----------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	19-01-2022
Primary Article Identifier	4008321159571
Declaration No. in SCIP database	In work

Download Data

File	
	Installation guide 334554_Instructions and safety advice for OUT KIT 30 mm x 21 mm
	CAD data 3-dim 313429_464x38x29 9900007

Product datasheet

	CAD data 3-dim 313461_464x38x29 9900007
	CAD data 3-dim 313499_464x38x29 9900007
	CAD data PDF 313400_464x38x29 9900007

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321159571	OUT KIT 21 S	Shipping carton box 20	486 mm x 153 mm x 195 mm	14.50 dm ³	2629.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.