Product datasheet



SIRIUS HRI 461 W S

SIRIUS HRI | High-pressure discharge lamps with reflector



Areas of application

- Concert lighting
- Club and disco
- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

Product family benefits

- Lightweight and compact reflector lamps
- Perfectly suited for small and lightweight moving heads
- Optimized burner design allows any burning position
- High luminance through very short arc and high pressure
- Bright light for brilliant light effects
- Long lifetime
- Easy lamp replacement
- Stable light output over the entire lifetime



April 7, 2024, 02:23:55 SIRIUS HRI 461 W S

Product datasheet

Technical data

Electrical data

Nominal wattage	461.00 W		
Nominal current	5.3 A		
Nominal voltage	83.0 V		

Photometrical data

Nominal luminous flux	24000 lm
Color temperature	7500 К
Color rendering index Ra	80

Dimensions & weight

Diameter	60.0 mm
Length	67.0 mm
Arc length	1.3 mm

Lifespan

Lifespan	1500 h
----------	--------

Additional product data

Category	VALUE
Capabilities	
Burning position	Any
Working distance	37.4 mm

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of Declaration	06-03-2024	
Primary Article Identifier	4052899532298 4052899553583	
Candidate List Substance 1	No declarable substances contained	
Declaration No. in SCIP database No declarable substances contained		

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, SIRIUS HRI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899532298	SIRIUS HRI 461 W S	Unpacked 1	- x - x -		140.00 g
4052899532304	SIRIUS HRI 461 W S	Shipping carton box 60	414 mm x 334 mm x 343 mm	47.43 dm ³	9904.00 g
4052899553583	SIRIUS HRI 461 W S	Folding carton box 1	87 mm x 87 mm x 103 mm	0.78 dm ³	188.00 g
4052899553590	SIRIUS HRI 461 W S	Shipping carton box 2	186 mm x 96 mm x 115 mm	2.05 dm ³	422.00 g
4052899553606	SIRIUS HRI 461 W S	Shipping carton box 20	507 mm x 203 mm x 264 mm	27.17 dm³	4701.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.