

HBO-IC Microlithography lamps for ASML i-line systems

Microlithography lamps for ASML i-line systems









Technical data

| | Electrical data | | | Dimensions & weight | | | |
|---------------------|--------------------|-----------------|-----------------|---------------------|--------------------|----------|---------|
| Product description | Nominal voltage | Nominal current | Type of current | Rated wattage | Nominal wattage | Diameter | Length |
| HBO 1003 W/PIL | 271 V | 258 A | DC | 70000 W | 700 W 1000 W | 290 mm | 1950 mm |
| HBO 1500 W/PIL | 230 V | 6500 A | DC | 150000 W | 150000 W | 460 mm | 2730 mm |
| HBO 2100 W/PIL | 240 V | 78 A | DC | 210000 W | 210000 W | 520 mm | 2400 mm |
| HBO 2500 W/PIL | 28.0 V | 90 A | DC | 250000 W | 250000 W | 620 mm | 3400 mm |
| HBO 3500 W/PIL | 230 V | 148 A | DC | 340000 W | 3400.00 W | 770 mm | 3600 mm |

| | | | | | Additional product data |
|---------------------|---------------------|---|------------------------------------|--------------------|-----------------------------------|
| Product description | Mountin g length | Length with base excl. base pins/connection | Light center length (LCL) | Electrode gap cold | Base anode (standard designation) |
| HBO 1003 W/PIL | 195.0 mm | 167.50 mm | 85.0 mm ¹⁾ | 3.0 mm | SFcX14-6/25 ²⁾ |
| HBO 1500 W/PIL | 273.0 mm | 240.00 mm | 118.0 mm | 4.0 mm | SFc30-6/25 ⁶⁾ |
| HBO 2100 W/PIL | 273.0 mm | 240.00 mm | 118.0 mm | 4.0 mm | |
| HBO 2500 W/PIL | | 312.50 mm | 149.0 mm | 7.0 mm | SFa30-6/50 ⁷⁾ |
| HBO 3500 W/PIL | | 320.00 mm | 154.0 mm | 4.5 mm | SFaX40-6/50 ⁷⁾ |

| | | Capabilities | | Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) |
|---------------------|---|----------------------|---------------------|--|
| Product description | Base cathode (standard designation) | Cooling | Burning position | Date of Declaration |
| HBO 1003 W/PIL | SFc15-6/25 ³⁾ | Forced ⁴⁾ | Other ⁵⁾ | 05-03-2024 |
| HBO 1500 W/PIL | SFc27-10/35 | Forced ⁴⁾ | Other ⁵⁾ | 05-03-2024 |
| HBO 2100 W/PIL | | | Other ⁵⁾ | 05-03-2024 |
| HBO 2500 W/PIL | SFc30-6.5/50 | Forced ⁴⁾ | Other ⁸⁾ | 05-03-2024 |
| HBO 3500 W/PIL | SFc32.5-6.7/50 | Forced ⁴⁾ | Other ⁸⁾ | 05-03-2024 |

| Product description | Primary Article Identifier | Candidate List Substance 1 | CAS No. of substance 1 | Safe Use Instruction |
|---------------------|--|----------------------------|------------------------|--|
| HBO 1003 W/PIL | 4050300461380 4050300967097 | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| HBO 1500 W/PIL | 4050300461465 4050300801308 4050300967103 4008321630872 | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| HBO 2100 W/PIL | 4050300800431 | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| HBO 2500 W/PIL | 4050300947396 | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| HBO 3500 W/PIL | 4008321355836 4008321355843 | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. |

| Declaration No. in | |
|---------------------|--|
| SCIP database | |
| b9c92b80-c1d8- | |
| 4748-8fda- | |
| 1d2d66728131 | |
| 31a5877e-d4ec- | |
| 4106-b4a4- | |
| a38a88565ee5 | |
| e22d7304-fdce-45fd- | |
| 8d2a-6aa5291d1a5b | |
| d36bbc5d-42c8- | |
| 43bc-a0b2- | |
| b64742e4d075 | |
| 910a2e30-b741- | |
| 4571-8470- | |
| 190c5ee7888d | |
| e65b3165-1b6a- | |
| 4da8-9fd8- | |
| 852bef40597d | |
| 7eee76a5-c4d5-4b9f- | |
| b456-ddffe12f4ebb | |
| | SCIP database b9c92b80-c1d8- 4748-8fda- 1d2d66728131 31a5877e-d4ec- 4106-b4a4- a38a88565ee5 e22d7304-fdce-45fd- 8d2a-6aa5291d1a5b d36bbc5d-42c8- 43bc-a0b2- b64742e4d075 910a2e30-b741- 4571-8470- 190c5ee7888d e65b3165-1b6a- 4da8-9fd8- 852bef40597d 7eee76a5-c4d5-4b9f- |

| Product description | Declaration No. in SCIP database |
|---------------------|----------------------------------|
| HBO 3500 W/PIL | 524e5e1f-27b9-4bac- |
| | 9f5e-5502c763034c |
| | 34bb99bc-0897- |
| | 4e24-883a- |
| | 0817db1e7cd5 |

 $^{^{1)}}$ Distance from end of base to tip of anode or cathode (cold)

²⁾ With cooling fins

³⁾ With thread (M6)

⁴⁾ Maximum permissible base temperature: 200 °C $\,$

⁵⁾ Anode underneath

⁶⁾ Cooling fins and cable connection (M 8)

 $^{^{7)}\,\}mathrm{With}$ cooling fins and cable connection (M 10)

⁸⁾ Anode on top

Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.