OSRAM

ORIGINAL - PLASTIC MF BASE -

Original spare part





The cost-effective original spare parts for motorcycles

With the ORIGINAL signal lamps for printed circuit boards, OSRAM offers a wide product range of original spare parts for motorcycles. These lamps provide OSRAM's reliable OEM quality and can be used for instrument and switch lighting.

Technical data

Product information

Order reference	2352MFX6
Application (Category and Product specific)	Auxiliary lamp


Electrical data

Power input	2.13 W
Nominal voltage	120 V
Nominal wattage	200 W
Power input tolerance	±10 %
Test voltage	13.5 V

Photometrical data

Luminous flux	118 lm
Luminous flux tolerance	±20 %

Dimensions & weight



Length	175 mm
Diameter	500 mm
Product weight	074 g

Colors & materials

Base color	Pale green

Lifespan

Lifespan B3	1500 h
Lifespan Tc	6000 h

Additional product data

Base (standard designation)	BX8.4d
-----------------------------	--------

Capabilities

Thickness of PCB	1.25 mm
Technology	AUX

Certificates & standards

ECE category	
ECE category	-

Country specific categorizations

Order reference	2352MFX6

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration 05-03-2024			
Primary Article Identifier	4008321097149 4008321011039 4062172046947		
Candidate List Substance 1	No declarable substances contained		
Declaration No. in SCIP database	In work		

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172046947	ORIGINAL - PLASTIC MF BASE 2352MFX6	Unpacked 1	- x - x -		
4062172046954	ORIGINAL - PLASTIC MF BASE 2352MFX6	Folding carton box 10	- x - x -		
4062172046961	ORIGINAL - PLASTIC MF BASE 2352MFX6	Shipping carton box 50	148 mm x 115 mm x 55 mm	0.94 dm³	122.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.













OSRAM