Product family datasheet



LEDriving PX-5

LED daytime running light for retrofit



LED pixel technology

Dynamic appearance thanks to faceted optic and dotted pixel technology

DRL

LED daytime running light compatible with a wide range of car models and easy to install

5200 K

For drivers who want to increase visibility during the day



Stylish highlights for your car

LEDriving PX-5 serves as a high performance and energyefficient daytime running light for retrofitting on your vehicle. With its patterned diode design of five LEDs, the LEDriving PX-5 gives your vehicle a modern and stylish look. This daytime running light system is compatible with a wide range of vehicle models and is easy to install. The careful design of the LEDriving system ensures a horizontal tilt of 10 degrees. In addition, the left-hand and right-hand lamps can be switched, thus making installation uncomplicated. Furthermore, the high color temperature of 5,200 Kelvin and long life of up to 5,000 hours provide endless driving pleasure with LEDriving PX-5. OSRAM provides a 3-year guarantee for this product. Note: LEDriving PX-5 is certified according to ECE, SAE and CCC regulations (ECE E4 approval; ECE R87 approval).

Product family datasheet

Technical data

	Product informatio n	Electrical data		Photometrical data		Dimensions & weight	Lifespan
Product description	Order reference	Nominal voltage	Nominal wattage	Color temper- ature	Luminous flux	Length	Guarantee
LEDriving PX-5	LEDDRL30 1	13.2 V	12.5 W	5200 K	300 lm	160.0 mm	3 years
LEDriving PX-5	LEDDRL30 1	13.2 V	12.5 W	5200 K	550 lm	160.0 mm	3 years

	Additional product data	Capabilities	Certificates & standards		
Product description	Connector to lamp	Technology	Approval marks – approval	Standards	
LEDriving PX-5	Wire Kit	LED	E4 approval	ECE R87	
LEDriving PX-5	Wire Kit	LED	E4 approval	ECE R87	

	Logistical data	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Product description	Commodity code	Date of Declaration	Primary Article Identifier	Candidate List Substance 1		
LEDriving PX-5	85122000900	06-03-2024	4052899170766	Lead		
LEDriving PX-5	85122000900	06-03-2024	4008321781215 4008321832382 4052899525498	Lead		

Product description	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
LEDriving PX-5	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	24fd4b7d-c774-46f3- 9b44-7c1767b813ea
LEDriving PX-5	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	7a05b6d4-2aed- 41c9-afdf- 7da8dfd39471

Product family datasheet

Download Data

	File
	User instruction 336028_LED Daytime Running Light Kit LEDDRL301 (User Manual)
1	User instruction 501779_LED Daytime Running Light Kit LEDDRL301 CL15 (User Manual)

Legal advice

ECE E4 approval

ECE R87 approval

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.









