

Product datasheet

P PIN 30 2.6 W/827 G9

PARATHOM LED PIN G9 | Special LED lamps



- Atmospheric accent lighting throughout the home Shops, hotels and restaurants Outdoor applications only in suitable luminaires

- Good all-around light emission Long lifetime of up to 15,000 h Four year guarantee



Product datasheet

Technical data

Electrical data

Rated wattage	2.60 W
Nominal wattage	2.60 W
Nominal voltage	220...240 V
Operating frequency	50/60 Hz
Max. lamp no. on circuit break. 10 A (B)	17
Max. lamp no. on circuit break. 16 A (B)	27
Nominal current	23 mA
Claimed equiv. conventional lamp power	30 W


Photometrical data

Nominal luminous flux	320 lm
Rated luminous flux	320 lm
Rated color temperature	2700 K
Color rendering index Ra	≥80
Light color (designation)	Warm White
Standard deviation of color matching	≤6 sdcn
Color temperature	2700 K
Luminous flux	320 lm
Lumen main.fact.at end of nom.life time	0.70

Light technical data

Beam angle	300 °
Starting time	< 0.5 s

Dimensions & weight



Overall length	47.00 mm
----------------	----------

Product datasheet

Diameter	15.0 mm
Outer bulb	T15
Product weight	6.00 g
Length	52.0 mm

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Lifespan

Nominal lamp life time	15000 h
Rated lamp life time	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.7

Additional product data

Base (standard designation)	G9
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear
Appropriate disposal acc. to WEEE	Yes
Successor EAN	4058075626041
Predecessor EAN	4058075811515

Capabilities

Dimmable	No
----------	----

Certificates & standards

Energy efficiency class	E
Energy consumption	3.00 kWh/1000h
Type of protection	IP20

Country specific categorizations

ILCOS	DRT/C-2,6/827-220-240-G9-15/52
Order reference	LEDPPIN30 CL 2,

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022

Product datasheet

Primary Article Identifier	4058075811515 4058075626041
Declaration No. in SCIP database	In work

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075626041	P PIN 30 2.6 W/827 G9	Shipping carton box 20 Pieces Folding carton box	150 mm x 122 mm x 77 mm	1.41 dm ³	246.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For further products and actual information concerning LED lamps see

▶ www.osram.com/ledlamps

For Guarantee see <https://>

▶ www.inventronics-light.com/multilevel-guarantees

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany