OSRAM XENARC NIGHT BREAKER LASER D4S

Brightest OSRAM xenon light





Up to 200% more brightness More light allows to see farther and therefore react sooner compared to the minimum legal standard



Up to 250 m long beam For better visibility



Up to 20% whiter light Close to laser look compared to the minimum legal standard



The most powerful xenon light from OSRAM

XENARC NIGHT BREAKER LASER is the brightest OSRAM xenon light for your motorcycle. This powerful lamp with efficient xenon technology ensures better visibility on the road, delivering up to 200% more brightness compared to the minimum legal standard. More light enables drivers to see farther and therefore react sooner. It also features an up to 250 m long beam and provides up to 20% whiter light (compared to the minimum legal standard) - close to a "laser look". Discover the pure performance of XENARC NIGHT BREAKER LASER - the most powerful xenon light from OSRAM, available in D1S, D2S, D3S and D4S. Please note: XENARC lamps should be replaced by a qualified mechanic.

Technical data


Electrical data

| Power input | 35 W |
|-----------------------|---------|
| Nominal voltage | 42.0 V |
| Nominal wattage | 35.00 W |
| Power input tolerance | ±3 % |
| Test voltage | 13.5 V |

Photometrical data

| Luminous flux | 3200 lm |
|-------------------------|---------|
| Color temperature | 4400 К |
| Luminous flux tolerance | ±15 % |

Dimensions & weight



| Length | 77.3 mm |
|----------------|---------|
| Diameter | 9 mm |
| Product weight | 16.30 g |
| Lifespan | |

| Lifespan B3 | 2000 h |
|-------------|--------|
| Lifespan Tc | 3000 h |

Additional product data

| Base (standard designation) | P32d-5 |
|-----------------------------|--------|
| , | |

Capabilities

| Technology | HID |
|------------|-----|

Certificates & standards

| ECE category | D4S ¹⁾ |
|---------------------------|-------------------|
| Approval marks – approval | E1 approval |

 $^{1)}$ To be operated only with approved electronic control gear $% ^{1)}$

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

| Date of Declaration | 06-03-2024 |
|----------------------------------|--|
| Primary Article Identifier | 4052899993235 4052899993198 4052899993174 4052899992993 4052899993211 |
| Candidate List Substance 1 | No declarable substances contained |
| Declaration No. in SCIP database | In work |

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|-----------------------------------|---------------------------------|---|----------------------|--------------|
| 4052899992993 | XENARC NIGHT BREAKER LASER D4S | Folding carton box 1 | 53 mm x 46 mm x 93 mm | 0.23 dm ³ | 39.00 g |
| 4052899993006 | XENARC NIGHT BREAKER LASER D4S | Shipping carton box 4 | 115 mm x 101 mm x 103 mm | 1.20 dm³ | 177.00 g |
| 4052899582583 | XENARC NIGHT BREAKER LASER D4S | Shipping carton box 48 | 371 mm x 256 mm x 232 mm | 22.03 dm³ | 2529.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Safety advice

XENARC lamps should be replaced by a qualified mechanic.

This product must only be operated with approved electronic control gear.

Legal advice

Light output compared to the minimum ECE R98/99 requirements

This product must only be operated with approved electronic control gear

XENARC lamps should be replaced by a qualified mechanic

Reduced UV emission | For projection headlights | ECE approval and DOT label

± 450 lm

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.





X







X

