

SFc104BB 12/CS 12/SKU



Product features and benefits

- Ceramic housings designed specifically for high temperature halogen and metal halide applications
- High quality contact materials for optimal mechanical and electrical properties
- UL recognized and CE certified

Areas of application

- Halogen Fixtures
- Metal Halide Fixtures
- Halogen Instrumentation
- Halogen Equipment

Product datasheet

Technical data

General product information

Product Number	69098	
Product Name	SFc104BB 12/CS 12/SKU	
CSA File No.	LR20904	
Old Part Number	F511939	

Electrical data

Maximum Wattage (W)	1500 W	
Maximum Voltage (V)	1000 V	
Voltage - Pulse Rated (kV)	25 kV	

Physical attributes

Length (in)	5.85 in	
Length (mm)	148.6 mm	
Width (in)	2.95 in	
Width (mm)	17.5 mm	
Height (in)	1.71 in	
Height (mm)	43.3 mm	
Rody Material Ceramic Stealite and Nickel Plated Steel		
Contact Material	Nickel Plated Nickel	
Wire Type	N/A	
Wire Gauge (AWG)	18-12 Comp AWG	

Additional product data

Lamp Base Reference	SFc10-4 with Pre-focus	
Maximum Operating Temperature (°C)	250 C	
Rohs Compliant	Yes	
Underwriters Laboratories File No.	E31557	

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69098	4052899127531	Shipping box (Case)	12	10.9 in x 8.1 in x 3 in	2.9 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Product datasheet

OSRAM does not accept liability for errors, changes and omissions.