

## HMI 18000W/SE GX51 1/CS 1/SKU



### Product features and benefits

- High intensity light providing true color performance with a CRI>90
- Longer life with heat dissipating round moly-foil design on lamps  $\geq 6000\text{W}$
- Mechanically robust with eXtreme Seal (XS) technology, up to  $450^{\circ}\text{C}$  at the pinch seal
- Capable of hot restrike ignition
- High color stability with average changes in color temperature during lamp life only  $1^{\circ}\text{K/hr}$
- Dimmable down to 40% with stable color using many electronic ballasts
- High energy efficiency providing up to 100 LPW
- HMI EVENT types offer enhanced brightness and color control as well as UV-stop technology

### Areas of application

- Studio, TV and film
- Professional Photography
- Solar Simulation

## Product datasheet

### Technical data

#### General product information

Product Number	54324
Product Name	HMI 18000W/SE GX51 1/CS 1/SKU
Ordering Abbreviation	HMI 18000W/SE GX51 1/CS 1/SKU
Brand Name	OSRAM
Family Brand Name	HMI
Application	Film, TV & Video Production. Studio Lighting
Product Remark	<ul style="list-style-type: none"><li>- SE=Single Ended</li><li>- s (Operating Position) = Vertical, base down</li><li>- Optimized lamp eXtreme Seal (XS) technology to withstand interior base temperatures of up to 450 degrees celsius.</li></ul>

#### Electrical data

Nominal Wattage	18000 W
Nominal Voltage	225 V
Current (A)	88 A
Type of Current	AC

#### Light technical data

Luminous Flux	1600000 lm
Luminous Efficacy (lm/W)	100 lm/W
Light Center Length - LCL (mm)	260 mm
Color Temperature	6000 K
Color Rendering Index	90
Average Rated Life	300 h

#### Physical attributes

Base	GX51 MOGUL BIPOST
Bulb Shape	T31
Maximum Overall Length (mm)	495 mm
Length l max. (mm)	495 mm
Diameter d (in)	3.937 in
Diameter d (mm)	100.00 mm
Distance a (mm)	260 mm
Electrode Gap - cold (mm)	44 mm
Reflector Coating	100.00

## Product datasheet

### Additional product data

<b>Operating Position</b>	s135
<b>Maximum Base Temperature (°C)</b>	450 C
<b>Cooling</b>	Convection
<b>Hot Restart</b>	Yes
<b>Lamp Type</b>	SINGLE END

### Packaging Information

<b>Product number</b>	<b>EAN/UPC</b>	<b>Packaging</b>	<b>Quantity</b>	<b>Outside dimensions l x w x h</b>	<b>Gross weight</b>
54324	4008321098955	Shipping box (Case)	1	28.1 in x 9.4 in x 9.4 in	7.2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.