

HMI 2500W/SE/XS 1/CS 1/SKU



Product features and benefits

- High intensity light providing true color performance with a CRI>90
- Longer life with heat dissipating round moly-foil design on lamps $\geq 6000\text{W}$
- Mechanically robust with eXtreme Seal (XS) technology, up to 450°C at the pinch seal
- Capable of hot restrike ignition
- High color stability with average changes in color temperature during lamp life only 1°K/hr
- Dimmable down to 40% with stable color using many electronic ballasts
- High energy efficiency providing up to 100 LPW
- HMI EVENT types offer enhanced brightness and color control as well as UV-stop technology

Areas of application

- Studio, TV and film
- Professional Photography
- Solar Simulation

Product datasheet

Technical data

General product information

Product Number	54070
Product Name	HMI 2500W/SE/XS 1/CS 1/SKU
Ordering Abbreviation	HMI 2500W/SE/XS 1/CS 1/SKU
Brand Name	OSRAM
Family Brand Name	HMI
Application	Film, TV & Video Production. Studio Lighting, Solar Simulation
Product Remark	<ul style="list-style-type: none">- SE=Single Ended- Optimized lamp eXtreme Seal (XS) technology to withstand interior base temperatures of up to 450 degrees celsius.

Electrical data

Nominal Wattage	2500 W
Nominal Voltage	115 V
Current (A)	25.6 A
Type of Current	AC

Light technical data

Luminous Flux	240000 lm
Luminous Efficacy (lm/W)	96 lm/W
Light Center Length - LCL (mm)	127 mm
Color Temperature	6000 K
Color Rendering Index	90
Average Rated Life	500 h

Physical attributes

Base	G38
Bulb Shape	GST60
Maximum Overall Length (mm)	225 mm
Length l (mm)	225 mm
Length l max. (mm)	225 mm
Diameter d (in)	2.362 in
Diameter d (mm)	60.00 mm
Distance a (mm)	127 mm
Electrode Gap - cold (mm)	14 mm

Product datasheet

Additional product data

Operating Position	Any
Maximum Base Temperature (°C)	450 C
Cooling	Convection
Hot Restart	Yes
Class	C (gas)
Lamp Type	SINGLE END

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54070	4050300284293	Shipping box (Case)	1	12.2 in x 6.3 in x 6.5 in	1.3 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.