

HSR 400/60 10/CS 1/SKU



Product features and benefits

- Proven, reliable technology for entertainment and architectural fixtures
- Designed with an outer quartz jacket providing compact and rugged construction
- High luminous efficacy of up to 90 lumens/watt

Areas of application

- Concert lighting
- Club & Disco
- Architecture & Architainment

Product datasheet

Technical data

General product information

Product Number	54102
Product Name	HSR 400/60 10/CS 1/SKU
Family Brand Name	HSR
Application	Entertainment, Effect and Architectural Lighting

Electrical data

Nominal Wattage	400 W
Nominal Voltage	67 V
Current (A)	6.9 A
Type of Current	AC

Light technical data

Luminous Flux	33000 lm
Average Luminance (cd/cm2)	20000 cd/cm2
Light Center Length - LCL (mm)	62 mm
Color Temperature	6000 K
Color Rendering Index	85
Average Rated Life	1000 h

Physical attributes

Base	GX9.5
Bulb Shape	T21
Maximum Overall Length (mm)	110 mm
Length l (mm)	110 mm
Diameter d (in)	0.906 in
Diameter d (mm)	23.00 mm
Distance a (mm)	62 mm
Electrode Gap - cold (mm)	5 mm

Additional product data

Operating Position	Any
Maximum Base Temperature (°C)	230 C
Cooling	Convection
Hot Restart	No

Packaging Information

Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
54102	4008321631503	Folding box (SKU)	1	1.8 in x 1.8 in x 5.9 in	0.1 lb
54102	4008321631510	Shipping box (Case)	10	9.6 in x 4.1 in x 6.8 in	1.4 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.