

## 4ARXS HSD 575W/72 10/CS 1/SKU



### Product features and benefits

- Proven, reliable technology for entertainment and architectural fixturesDesigned with an outer quartz jacket providing compact and rugged construction
- Designed with an outer quartz jacket providing compact and rugged construction
- High luminous efficacy of up to 90 lumens/watt
- 4ARXS ("For Architainment eXtreme Seal") are designed to withstand temperatures up to 450°C at the pinch seal and provide longer lamp life of up to 3,000 hrs (when operated on an ECG)

### Areas of application

- Concert lighting
- Club & Disco
- Architecture & Architainment

Technical data

General product information

Product Number	54129
Product Name	4ARXS HSD 575W/72 10/CS 1/SKU
Family Brand Name	4ArXS HSD
Application	Entertainment, Effect and Architectural Lighting
Product Remark	– Optimized lamp eXtreme Seal (XS) technology to withstand interior base temperatures of up to 450 degrees celsius.

Electrical data

Nominal Wattage	575 W
Nominal Voltage	88 V
Current (A)	7.4 A
Type of Current	AC

Light technical data

Luminous Flux	45000 lm
Light Center Length - LCL (mm)	65 mm
Color Temperature	7200 K
Color Rendering Index	85
Average Rated Life	3000 h

Physical attributes

Base	GX9.5
Bulb Shape	T30
Maximum Overall Length (mm)	135 mm
Length l (mm)	135 mm
Length l max. (mm)	135 mm
Diameter d (in)	1.181 in
Diameter d (mm)	30.00 mm
Distance a (mm)	65 mm
Electrode Gap - cold (mm)	7 mm

Additional product data

Operating Position	Any
Maximum Base Temperature (°C)	450 C
Cooling	Convection

Product datasheet

Hot Restart	No
Lamp Type	SINGLE END

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54129	4008321625809	Folding box (SKU)	1	2.2 in x 2.2 in x 6.8 in	0.2 lb
54129	4008321625816	Shipping box (Case)	10	11.6 in x 4.9 in x 7.5 in	2.4 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.