

HBO 500W/48.5V/B 10/CS 1/SKU



Product features and benefits

- High spectral intensity with peak irradiance at 365nm wavelength, making it ideal for microlithography
- Ceramic housings designed specifically for high temperature halogen and metal halide applications for optimal exposure and throughput
- Designed for long lasting performance
- Qualified with ASML

Areas of application

- Semiconductor

Product datasheet

Technical data

General product information

| Product Number | 69206 | | | |
|-------------------|--|--|--|--|
| Product Name | HBO 500W/48.5V/B 10/CS 1/SKU | | | |
| Family Brand Name | НВО | | | |
| Application | Semiconductor | | | |
| Product Remark | Cathode base with M 5x 0.9 thread Lamp service life is defined with a switch-on/switch off duty cycle of 12hours ON / 30 minutes OFF. Lamp anode base (hexagon) with thread M5x0.9 | | | |

Electrical data

| Nominal Wattage | 500 W |
|-----------------|--------|
| Nominal Voltage | 48.5 V |
| Current (A) | 10.3 A |
| Type of Current | DC |

Light technical data

| Average Luminance (cd/cm2) | 64000 cd/cm2 | |
|---|--------------|--|
| Radiant intensity in 350-450 nm range (mW/sr) | 5800 mW/sr | |
| Radiant Power in 350-450 nm range (W) | 60 W | |
| Light Center Length - LCL (mm) | 78.5 mm | |
| Average Rated Life | 800 h | |

Physical attributes

| Base Anode | SFcX13-5/20 | | |
|------------------------------------|---------------|--|--|
| Base Cathode | SFcY 13-15/20 | | |
| Maximum Overall Length (mm) 180 mm | | | |
| Length l1 (mm) | 180 mm | | |
| Length l1 max. (mm) | 180 mm | | |
| Diameter d (in) | 1.142 in | | |
| Diameter d (mm) | 29.00 mm | | |
| Distance a (mm) | 78.5 mm | | |
| Electrode Gap - cold (mm) | 3 mm | | |

Additional product data

| Operating Position | Vertical, anode down |
|--------------------|----------------------|
|--------------------|----------------------|

Product datasheet

| Maximum Base Temperature (°C) | 200 C | |
|-------------------------------|--------------|--|
| Cooling | Convection | |
| Lamp Type | DOUBLE ENDED | |

Packaging Information

| Product number | EAN/UPC | Packaging | Quantity | Outside dimensions l x w x h | Gross weight |
|----------------|---------------|---------------------|----------|------------------------------|--------------|
| 69206 | 4050300275819 | Shipping box (Case) | 1 | 8.5 in x 3.7 in x 2.8 in | 0.7 lb |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.