

XBO 150W/4 20V 10/CS 1/SKU



Product features and benefits

- High luminance / radiance with intense point source
- Broad, continuous spectral distribution
- High color rendering > 95
- High arc stability
- DC operation

Areas of application

- Endoscopy
- Microscopy
- Surgical Headlamps
- Fiber Illumination
- Solar Simulation
- Imaging & scanning

Technical data

General product information

Product Number	69238
Product Name	XBO 150W/4 20V 10/CS 1/SKU
Family Brand Name	XBO
Application	Microscopy
Product Remark	<ul style="list-style-type: none">- Lamp uses Suprasil quartz glass.- s (Operating Position) = Vertical, base down- This lamp has positive pressure even when cold. Please read safety/warning instructions before using this lamp.- Distance a is from end of base to the respective electrode tip (cold.- With vertical operating position: anode(+) on top.

Electrical data

Nominal Wattage	150 W
Current (A)	7.5 A
Type of Current	DC

Light technical data

Luminous Flux	3000 lm
Average Luminance (cd/cm2)	15000 cd/cm2
Luminous Intensity (cd)	300 cd
Luminous Area (mm)	0.5 x 2.2 mm
Light Center Length - LCL (mm)	57 mm
Color Temperature	6000 K
Color Rendering Index	98
Average Rated Life	1200 h
Average Life, Vertical	1200 h

Physical attributes


Base Anode	SFc12-4
Base Cathode	SFcX12.4
Maximum Overall Length (mm)	150 mm
Length l1 (mm)	150 mm
Length l1 max. (mm)	150 mm
Diameter d (in)	39.331 in
Diameter d (mm)	999.00 mm

Product datasheet

Distance a (mm)	57 mm
-----------------	-------

Additional product data

Operating Position	s 15
Maximum Base Temperature (°C)	230 C
Forced Cooling	Required
Hot Restart	Yes
Lamp Type	DOUBLE ENDED



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69238	4050300508382	Folding box (SKU)	1	8.8 in x 3.7 in x 2.4 in	0.4 lb
69238	4050300508399	Shipping box (Case)	10	12 in x 9.3 in x 7.9 in	5 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.