

XSTAGE 4000W OFR 1/CS 1/SKU



Product features and benefits

- High luminance (point source) with rugged design for spotlight applications
- Color temperature approximately 6000K simulates daylight
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart

Areas of application

- Digital
- Film
- Spotlights
- Searchlights
- Solar Simulation

Product datasheet

Technical data

General product information

Product Number	69484		
Product Name	XSTAGE 4000W OFR 1/CS 1/SKU		
Family Brand Name	XBO		
Application	Event & Architainment Lighting, Follow Spots, Sky Tracker		
Product Remark	 OFR=Ozone Free This lamp has positive pressure even when cold. Please read safety/warning instructions before using this lamp. Distance a is from end of base to the respective electrode tip (cold. With vertical operating position: anode(+) on top. 		

Electrical data

Nominal Wattage	4000 W		
Nominal Voltage	30 V		
Current (A)	130 A		
Current Control Range (A)	80-135 A		
Type of Current	DC		

Light technical data

Luminous Flux	150000 lm		
Average Luminance (cd/cm2)	120000 cd/cm2		
Luminous Intensity (cd)	17000 cd		
Luminous Area (mm)	1.9 x 5.0 mm		
Light Center Length - LCL (mm)	120 mm		
Color Temperature	6000 K		
Color Rendering Index	98		
Average Rated Life	650 h		
Average Rated Life - Horizontal (hr)	1000 hr		

Physical attributes

Base Anode	SFaX27-9.5		
Base Cathode	SFc28-27		
Bulb Shape	K0162		
Maximum Overall Length (mm)	315 mm		
Length l1 (mm)	315 mm		

Product datasheet

Length l1 max. (mm)	315 mm
Diameter d (in)	2.362 in
Diameter d (mm)	60.00 mm
Distance a (mm)	120 mm
Electrode Gap - cold (mm)	6 mm

Additional product data

Operating Position	s90		
Maximum Base Temperature (°C)	230 C		
Cooling	Required		
Hot Restart	Yes		
Lamp Type	XENON		

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69484	4008321288844	Shipping box (Case)	1	23.2 in x 9.2 in x 9 in	4.1 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.