OSRAM

LEDriving FL H10

LED replacement for conventional fog lamps





Cool White color temperature of 6,000 K

Better visibility in foggy situations with a perfect color match for xenon and LED headlights. Signs, obstacles and hazards can be recognized sooner.

Superior brightness

More light allows to see farther and therefore react sooner with reduced glaring thanks to an optimized light distribution Ultra compact LED replacement for conventional H10 fog lamps as socket solution

Easy installation with optimized compatibility



New OSRAM LED fog lamps to increase safety and performance

The latest generation of OSRAM LED fog lamps provides an even more convenient solution in order to replace and upgrade existing halogen fog lamps: With its ultra compact dimensions, the OSRAM LEDriving FL provides optimized compatibility as well as easy plug & play installation. Upgrading with state-of-the-art LED technology and a color temperature of 6,000 K for a stylish cool white look as well as improved visibility. These LED products offer a perfect color match with xenon and LED headlights and are for conventional H10 fog lamps. A pair of new LEDriving FL lamps, comes with a 3-year OSRAM guarantee as well as with a long service life by less energy consumption. For precise guarantee conditions please refer to www.osram.com/amguarantee. Please note: These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Technical data

	Product info	Product information				Electrical data				
Product description	Order reference	Product type (off- road vs. on-road)	Application (Category and Product specific)		Power input	Te: vol	st tage	Nominal wattage	Nominal voltage	
LEDriving FL ≙ H10	9745CW	Off-road ≙ H10	Mainly used light applica		3			8.20 W	12.0 V	
	Photometric	Photometrical data Dimensions Life		Lifespan	ifespan			Capabilities		
Product description	Luminous flux	Luminous flux tolerance	Diameter	Lifespan	Lifespan Tc Lifespan B3			Technology		
LEDriving FL ≙ H10	720 lm	±15 %	17.2 mm	5000 h	250) h	LED			
		tal information according Art.	n . 33 of EU Regul	lation (EC)	1907/200	6				
Product description	Date of Deci		,		eclaration No. in CIP database					
LEDriving FL ≜ H10	06-03-2024	4 4 4 4	052899605060 062172033329 059089376892 059089349568 059089400412 062172401913	work						

Download Data

File



Brochures

LEDriving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Detailed guarantee terms can be found at www.osram.com/am-guarantee.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.









