

## BASIC Linear G3

### Linear Light Engines



#### Product family features

- Module efficacy: up to 168 lm/W
- Available with luminous flux: 770 lm, 1,100 lm on 280 mm
- Available with luminous flux: 1,550 lm, 2,200 lm on 560 mm
- Available with luminous flux: 3,100 lm, 4,400 lm on 1,120 mm
- Average lifetime (L80 B50): > 50,000 h (temperature at  $T_c = 50^\circ\text{C}$ )
- Color rendering index: > 80
- CE marked, ENEC certified

#### Product family benefits

- Slim luminaire design by small and flexible form factor
- Adjustable luminous flux, efficacy and lifetime
- Powerful system with cost efficient OPTOTRONIC/ELEMENT driver family

#### Areas of application

- Office
- Industry

## Product family datasheet

---

### Application advice

For more detailed application information and graphics please see product datasheet.

---

### Sales and Technical Support

Sales and Technical Support [www.osram.com](http://www.osram.com)

---

### Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.