

Product family datasheet

SubstiTUBE PRO EM

High performance LED tubes for electromagnetic control gears (CCG), shatterproof



Product family datasheet

Technical data

	Electrical data						
Product description	Operating frequency	Claimed equiv. conventional lamp power	Nominal current	Nominal wattage	Rated wattage	Nominal voltage	Max. lamp no. on circuit break. 16 A (B)
ST8PRO-EM 1030 W/840 9100 mm	50...60 Hz	30 W	49 mA				
ST8PRO-EM 1270 W/840 1200 mm	50...60 Hz	36 W	60 mA				
ST8PRO-EM 1210 W/840 1100 mm	50...60 Hz	38 W	0.057 A	12.10 W	12.10 W	220...240 V	126
		Photometrical data					
Product description	Max. lamp no. on circuit break. 10 A (B)	Light color (designation)	Lumen main.fact.at end of nom.life time	Color temperature	Rated luminous flux	Standard deviation of color matching	Color rendering index Ra
ST8PRO-EM 1030 W/840 9100 mm		Cool White					
ST8PRO-EM 1270 W/840 1200 mm		Cool White					
ST8PRO-EM 1210 W/840 1100 mm	79	Cool White	0.70	4000 K	2000 lm	≤5 sdc _m	83
		Light technical data		Dimensions & weight			
Product description	Nominal luminous flux	Beam angle	Starting time	Product weight	Overall length	Outer bulb	Length
ST8PRO-EM 1030 W/840 9100 mm		190 °		144.00 g	908.00 mm		
ST8PRO-EM 1270 W/840 1200 mm		190 °		183.00 g	1212.00 mm		
ST8PRO-EM 1210 W/840 1100 mm	2000 lm	190 °	< 0.5 s	164.00 g	1061 mm	T8	1061 mm
		Temperatures & operating conditions	Lifespan				Additional product data
Product description	Diameter	Ambient temperature range	Lumen maintenance at end of service life	Number of switching cycles	Rated lamp life time	Nominal lamp life time	Mercury-free
ST8PRO-EM 1030 W/840 9100 mm		-20...+50 °C	0.7				Yes
ST8PRO-EM 1270 W/840 1200 mm		-20...+50 °C	0.7				Yes

Product family datasheet

Product description	Diameter	Temperatures & operating conditions	Lifespan				Additional product data
		Ambient temperature range	Lumen maintenance at end of service life	Number of switching cycles	Rated lamp life time	Nominal lamp life time	Mercury-free
ST8PRO-EM 1210 W/840 1100 mm	26.7 mm	-20...+50 °C	0.70	200000	60000 h	60000 h	Yes

				Certificates & standards			Environmental information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
Product description	Predecessor EAN	Successor EAN	Base (standard designation)	Energy consumption	Energy efficiency class	Type of protection	Date of Declaration
ST8PRO-EM 1030 W/840 9100 mm	4058075454125	4058075612198		11.00 kWh/1000h	C		25-07-2022
ST8PRO-EM 1270 W/840 1200 mm	4058075454200	4058075612273		13.00 kWh/1000h	C		18-04-2022
ST8PRO-EM 1210 W/840 1100 mm	4058075454163	4058075612235	G13	13 kWh/1000h	C	IP20	18-04-2022

Product description	Primary Article Identifier	Declaration No. in SCIP database
ST8PRO-EM 1030 W/840 9100 mm	4058075454125 4058075612198	In work
ST8PRO-EM 1270 W/840 1200 mm	4058075454200 4058075612273	In work
ST8PRO-EM 1210 W/840 1100 mm	4058075454163 4058075612235	In work

Product family datasheet



ST8PRO-EM 1030 W/840 9100 mm,
ST8PRO-EM 1270 W/840 1200 mm,
— ST8PRO-EM 1210 W/840 1100 mm

Equipment / Accessories

- Suitable for operation with low-loss and conventional control gears

Application advice

For more detailed application information and graphics please see product datasheet.

Product family datasheet

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075454125	ST8PRO-EM 1030 W/840 9100 mm	Shipping carton box 10	1048 mm x 210 mm x 115 mm	25.31 dm ³	2298.00 g
4058075612198	ST8PRO-EM 1030 W/840 9100 mm	Shipping carton box 10	1048 mm x 210 mm x 115 mm	25.31 dm ³	2298.00 g
4058075612273	ST8PRO-EM 1270 W/840 1200 mm	Shipping carton box 10	1352 mm x 210 mm x 115 mm	32.65 dm ³	2809.00 g
4058075612235	ST8PRO-EM 1210 W/840 1100 mm	Shipping carton box 10	1195 mm x 210 mm x 115 mm	28.86 dm ³	2634.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany