OSRAM

LEDriving SMART CANBUS (OFFROAD)

Accessories for LED retrofit lamps





Error message free
Bypasses the vehicle's error
detection



Robust and resistant
No disturbing flickering in
the headlamp



3-year OSRAM GuaranteeSystematic quality assurance measures underpin the

premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.



Duopack

Two Canbus in one box







Convert from halogen to LED with original OSRAM accessories

Some vehicles report a fault in the exterior lighting when LED lamps are used. With the OSRAM LEDriving Smart Canbus series, potential error messages in the on-board system are avoided.

These error messages can occur when converting to LED lamps, as these have a lower current consumption than, for example, halogen lamps and therefore the vehicle's existing fault detection mechanism will be activated.

Only the combination of OSRAM LED lamps in conjunction with the official OSRAM accessories - LEDriving ADAPTER, LEDriving SMART CANBUS, LEDriving CAPs and LEDriving ERROR CANCELER is approved for the

operation of our LED lamps.

Details, in particular on the combination of OSRAM accessories and the street-legal NIGHT BREAKER LED and TRUCKSTAR LED lamps, can be found on the respective product pages under: NIGHT BREAKER LED Kompatibilitätslisten | Automotive (osram.de) or Automotive | OSRAM Automotive

Technical data

	Electrical Data	Lifetime Data		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Product description	Nominal wattage	Lifespan B3	Lifespan Tc	Primary article identifier	Candidate list substance 1
LEDriving Canbus Control LEDSC01	12.00 W	2500 hr	2500 hr	4062172191234 4062172176439	Lead
LEDriving Canbus Control LEDSC02-1	16.00 W	2500 hr	2500 hr	4062172176460 4062172191173	Lead
LEDriving Canbus Control LEDSC03	12.00 W	2500 hr	2500 hr	4062172176491 4062172191203	Lead
LEDriving Canbus Control LEDSC03-1	12.00 W	2500 hr	2500 hr	4062172278249	No declarable substances contained
LEDriving Canbus Control LEDSC04- 2HB ¹⁾	15.00 W	2500 hr	2500 hr	4062172400725	Lead
LEDriving Canbus Control LEDSC05- 2HB ²⁾	15.00 W	2500 hr	2500 hr	4062172400756	Lead
LEDriving Canbus Control LEDSC06- 2HB ³⁾	15.00 W	2500 hr	2500 hr	4062172400787	Lead

Product description	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
LEDriving Canbus Control LEDSC01	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	3a3de6c9-42c9- 4c29-aa1c- 7b39300c74bf
LEDriving Canbus Control LEDSC02-1	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	a280f1b6-dc66- 420e-a55a- b93b3613f1f7
LEDriving Canbus Control LEDSC03	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	c150c4e9-3874-41cf- b147-73065ae9487a b228c675-685f- 4439-b56b- d61c0e60da8b
LEDriving Canbus Control LEDSC03-1			No declarable substances contained
LEDriving Canbus Control LEDSC04- 2HB ¹⁾	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	68e55d1b-c2d0- 485e-91dc- 10665708cd08
LEDriving Canbus Control LEDSC05- 2HB ²⁾	7439-92-1		In work

Product description	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
LEDriving Canbus Control LEDSC06- 2HB ³⁾	7439-92-1		In work

 $^{^{1)}\,\}mathrm{High}\text{-}$ and Low Beam, 12V H4 & H19 LED

 $^{^{2)}}$ High Beam, Low Beam, Fog Light, 12V, H8-LED, H9-LED, H11-LED, H16 LED Lamps

³⁾ High Beam, Low Beam, Fog Light, 12V, H10-LED, HB3-LED, HB4-LED, H16-LED Lamps

Download Data

	File
Z	User instruction LEDSC01 Astra
大	User instruction LEDSC03 1 series (EN)
Z	User instruction GPRS_Safety symbols instructions
Z	User instruction LEDSC01 A-Klasse (EN)
大	User instruction LEDSC02 1 A4
太	User instruction LEDSC03 LEDSC03 1 2 series
<u>**</u>	User instruction LEDSC03 3 series (EN)
7	User instruction LEDriving SMART CANBUS

Safety advice

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

Legal advice

1) Approved LED light source applies to all vehicle models to specific light functions and further restrictions in the respective country. Must not be used behind red and/or yellow colored glass.

For more details see www.osram.com/nb-led2) For precise conditions please refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaime

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.