OSRAM

LEDriving SMART CANBUS (OFFROAD) LEDSC01

Accessories for LED retrofit Lamps





Error message free
Bypasses the vehicle's error
detection



Robust and resistant
No disturbing flickering in
the headlamp



3-year OSRAM Guarantee2)
Systematic quality assurance
measures underpin the
premium workmanship and
functionality of our products.
Innovative technology and
excellent quality really pay

dividends for our customers.



DuopackTwo Canbus in one box



Convert from halogen to LED with original OSRAM accessories

Some vehicles report a fault in the exterior lighting when LED lamps are used. With the OSRAM LEDriving Smart Canbus series, potential error messages in the on-board system are avoided. These error messages can occur when converting to LED lamps, as these have a lower current consumption than, for example, halogen lamps and therefore the vehicle's existing fault detection mechanism will be activated. Only the combination of OSRAM LED lamps in conjunction with the official OSRAM accessories - LEDriving ADAPTER, LEDriving SMART CANBUS, LEDriving CAPs and LEDriving ERROR CANCELER is approved for the operation of our LED lamps.Details, in particular on the combination of OSRAM accessories and the street-legal1) NIGHT BREAKER LED and TRUCKSTAR LED lamps, can be found on the respective product pages under: NIGHT BREAKER LED Kompatibilitätslisten | Automotive (osram.de) or Automotive | **OSRAM** Automotive

Technical data


Product information

Order reference	LEDSC01
Application (Category and Product specific)	Accessories for LED retrofits

Electrical data

Nominal wattage	12.00 W

Dimensions & weight



Product weight	193.80 g
Length	390.0 mm

Lifespan

Lifespan B3	2500 h
Lifespan Tc	2500 h

Capabilities

Country specific categorizations

Order reference	LEDSC01
-----------------	---------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of Declaration	07-03-2024	
Primary Article Identifier	4062172176439 4062172191234	
Candidate List Substance 1	Lead	

CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	3a3de6c9-42c9-4c29-aa1c-7b39300c74bf

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172176439	LEDriving Canbus Control LEDSC01	Folding carton box 2	105 mm x 60 mm x 160 mm	1.01 dm ³	897.00 g
4062172201018	LEDriving Canbus Control LEDSC01	Shipping carton box 4	130 mm x 114 mm x 175 mm	2.59 dm ³	967.00 g
4062172201025	LEDriving Canbus Control LEDSC01	Shipping carton box 48	365 mm x 281 mm x 387 mm	39.69 dm³	12407.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
大	User instruction LEDSC03 1 series (EN)
7	User instruction LEDSC01 A-Klasse (EN)

Safety advice

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

Legal advice

1) Approved LED light source applies to all vehicle models to specific light functions and further restrictions in the respective country. Must not be used behind red and/or yellow colored glass.

For more details see www.osram.com/nb-led

2) For precise conditions please refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM