EM FIT 75/220...240/1A6 CS L

ELEMENT EM FIT SELV | Linear / Area Constant Current – Non dimmable



Product family features

- Line frequency: 50 Hz | 60 Hz
- Supply voltage: 220...240 V
- Lifetime: up to 50,000 h (temperature at T_C max. = -10 °C, max 10% failure rate)
- SELV driver
- Wide output voltage range
- Fixed output (no dimming)

Product family benefits

- Small housing design
- Flexible current setting (DIPswitch – 4 currents)
- Enhanced safety due to overload, overtemperature, short-circuit protection
- High efficiency
- Long lasting and high reliability
- High light quality due to low ripple current

Areas of application

- Linear and area lighting
- Shop lighting
- Industry lighting
- Offices, Public buildings, Supermarkets
- Suitable for luminaires of protection class I and II

© 2024, Inventronics GmbH. All rights reserved. Inventronics is a licensee of the OSRAM brand. OSRAM is a trademark of ams OSRAM.

Technical data

Electrical data

Nominal input voltage	220…240 V
Mains frequency	50/60 Hz
Input voltage AC	198…264 V
Current set	DipSwitch
Power factor λ	0.95 [1)]
Efficiency in full-load	89 % [2)]
Device power loss	9.7 W [3)]
Inrush current	60 A [4)]
Max. ECG no. on circuit breaker 10 A (B)	7
Max. ECG no. on circuit breaker 10 A (C)	12
Max. ECG no. on circuit breaker 16 A (B)	12
Max. ECG no. on circuit breaker 16 A (C)	20
Max. ECG no. on circuit breaker 25 A (B)	18
Max. ECG no. on circuit breaker 25 A (C)	31
Surge capability (L/N-Ground)	2 kV [5)]
Surge capability (L-N)	1 kV
Nominal output voltage	27…51 V [6)]
Nominal output current	1300 / 1400 / 1500 / 1600 mA [7)]
Output PSTLM	≤1
Output SVM	≤0.4
Nominal output power	35.1…81.6 W
Maximum output power	81.6 W
U-OUT (working voltage)	< 60 V
Total harmonic distortion	< 20 % [8)]
Output current tolerance	±7.5 %
Galvanic isolation	SELV
Output ripple current (100 Hz)	< 10 % [9)]

1) Half load at 230 V/50 Hz

2) at 230 V, 50 Hz

3) At 230 V

4) t_{width} = 190 µs typical (measured at 50 % I_{peak})

5) L/N – PE acc to EN 61547 Cluase 5.7


6) At 1300/1400/1500/1600 mA output current

7) ±7.5%


8) At full load, 230 V, 50 Hz / see graphs

9) Ripple average at 100 Hz


© 2024, Inventronics GmbH. All rights reserved. Inventronics is a licensee of the OSRAM brand. OSRAM is a trademark of ams OSRAM.




EM FIT 75 220 240 1A6 CS L Operating Window



EM FIT 75 220 240 1A6 CS L Typical Efficiency vs Load




EM FIT 75 220 240 1A6 CS L Typical Power Factor vs Load




EM FIT 75 220 240 1A6 CS L Typical THD vs Load

© 2024, Inventronics GmbH. All rights reserved. Inventronics is a licensee of the OSRAM brand. OSRAM is a trademark of ams OSRAM.

Dimensions & weight





Mounting hole spacing, length	270.0 mm
Product weight	210.00 g
Cable cross-section, input side	0.5…1.5 / 0.75…1.5 mm² [1]
Cable cross-section, output side	0.5…1.5 / 0.75…1.5 mm² [1]
Wire preparation length, input side	7…8 mm
Wire preparation length, output side	7…8 mm
Length	280.0 mm
Width	30.0 mm
Height	21.0 mm

[1] Solid or flexible leads

Colors & materials

Casing material	Metal

Temperatures & operating conditions

Ambient temperature range	-20…+50 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Temperature range at storage	-40…85 °C
Permitted rel. humidity during operation	5…90 % [1]

[1] Non-condensing

Lifespan

ECG lifetime	35000 / 50000 h [1]

[1] At maximum T_c = 75°C / 10% failure rate / At maximum T_c = 65°C / 10% failure rate

Additional product data

Encapsulated	No

© 2024, Inventronics GmbH. All rights reserved. Inventronics is a licensee of the OSRAM brand. OSRAM is a trademark of ams OSRAM.

Capabilities

Dimmable	No
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
Short-circuit protection	Automatic reversible
No-load proof	Yes
Intended for no-load operation	No
Max. cable length to lamp/LED module	2.0 m [1)]
Suitable for fixtures with prot. class	I
Number of channels	1

[1)] Output wires must be routed as close as possible to each other

Programming

Box programming	No
Tuner4TRONIC	No
Tuner4TRONIC Field App	No
Programming device	DIPswitch

Certificates & standards

Approval marks – approval	CE / CCC / ENEC / RCM / EAC / UKCA
Standards	Acc. to IEC 61347-1/Acc. to IEC 61347-2-13/Acc. to IEC 62384/Acc. to IEC 61000-3-2/Acc. to IEC 61547/CISPR 15/EN 55015
Type of protection	IP20

Logistical data

Commodity code	85044083900

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of Declaration	19-05-2023
Primary Article Identifier	4062172220033
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	39ca20a0-60fd-4c7b-8120-5af2ddea52d9

© 2024, Inventronics GmbH. All rights reserved. Inventronics is a licensee of the OSRAM brand. OSRAM is a trademark of ams OSRAM.

Product datasheet

Download Data

	File
	User instruction ELEMENT LED Power Supply
	Certificates OT constant current EAC DE PA01 B 34987 21 071221
	Certificates EM FIT CS L CB NL 74845 071221
	Certificates EM FIT CS L&D CS L ENEC 35 120653 071221
	Certificates EM FIT 60 75 CS L CCC 2021171002004191 071221
	Certificates NSW27964 2 certificate of EM FIT CS L

Ecodesign regulation information:

Intended for use with LED modules.
The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172220033	EM FIT 75/220...240/1A6 CS L	Shipping carton box 20	375 mm x 320 mm x 75 mm	9.00 dm^3	4779.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2024, Inventronics GmbH. All rights reserved. Inventronics is a licensee of the OSRAM brand. OSRAM is a trademark of ams OSRAM.