Product family datasheet

OSRAM

LEDriving SL R10W

Ideal replacement for any vehicle



Suitable for various vehicle interior and exterior applications

Available in Cool White



Reliable OSRAM quality stands for less lamp replacements

4-year guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for R10W

LEDriving SL R10W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional R10W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

	Electrical Data					Photom etric Data
Product description	Power input	Nominal voltage	Nominal wattage	Power input toleranc e	Test voltage	Nominal luminou s flux
LEDriving SL ≙ R10W	1.24 W	12 V	1 W	±20 %	13.5 V	125 lm

Physical Attributes	Physical Attributes & Dimensions					
Lamp base	Length	Diamete	er Diamet	ter		
BA15s	37.5 mm	19.0 mn	n 19.0 m	m		
Lifetime Data	Lifetime Data		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Lifespan B3	Lifespan Tc	Primary article identifier	Candidate list substance 1			
1500 hr	4000 hr	4062172222846 4062172222822 4062172401296	Lead			
	Lifespan B3	Lamp base Length BA15s 37.5 mm Lifetime Data Lifespan B3 Lifespan Tc	Lifetime Data Lifetime Data Lifespan B3 Lifespan Tc 1500 hr Lifetime Data Lifetime Data Lifespan B3 Lifespan Tc 1500 hr Lifetime Data Lifetime Data Lifetime Data Lifetime Data Environmental & Regulation (EC) 1907 Regulation (EC) 1907 Lifetime Data Authorized Lifetime Data Lifetime Data	Lamp base Length Diameter Diameter BA15s 37.5 mm 19.0 mm 19.0 mm 19.0 mm Lifetime Data Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) Lifespan B3 Lifespan Tc identifier substance 1 1500 hr 4000 hr 4062172222846 Lead 4062172222822		

Product description	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
LEDriving SL ≜ R10W	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	acfdb47e-fe18-4536- a610-cbb4826f1ca3 785bd7fd-0d7a- 4942-b9cd- 6c9b06b40981 ae611627-677a- 439a-bb49- 72f598538ea1

Product family datasheet

Download Data

File



User instruction

GPRS_Safety symbols instructions



Brochures

LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatible

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.