Product family datasheet

OSRAM

LEDriving XTR H7

Superior LED headlight bulbs for off-road use



XTR-EME BRIGHTNESS Perfect cool white color temperature of 6,000K with a superior light output, providing a stylish and modern look.



GERMAN DESIGN With our state-of-the-art BeamGuide technology and an intelligent product design made in Germany, an optimized light distribution is achieved for a more focused and enhanced beam

pattern.



TOP TECHNOLOGY

Our OSRAM top technology ensures, that the thermal management is boosted by active cooling through an optimized high-speed silent fan with up to 10,000 RPM.



Long lifetime Without compromising, our proven top grade materials offer extreme levels of performance with superior durability and long life spans with an additional approx. 70% lower energy consumption compared to conventional bulbs.

Superior LED headlight bulbs for off-road use



Featuring a color temperature of 6,000 K and a very compact design, the OSRAM LEDriving XTR replacement lamps provide an easy plug and play solution to upgrade your conventional car headlights with cool white LED light – providing a stylish and modern look for your vehicle. With our state-of-the-art technology and an intelligent product design, our lamps are the ideal companion to see further and detect obstacles sooner. The name OSRAM stands for quality without compromise, which is why we are proud to offer a 3-year guarantee¹⁾ on our products and a lifelong support.

© 2025, OSRAM GmbH. All rights reserved.

Product family datasheet

Technical data

_

	Electrical Data					Photometric Data
Product description	Power No input	ominal voltage Nominal wattage		Test voltage		Nominal luminous flux
LEDriving XTR \doteq H7	18 W 12	V	18 W	13	.2 V	1750 lm
		Physical Attribut	es & Dimensions		Lifetime	e Data
Product description	Luminous flux tolerance	Diameter	Diameter		Lifespa B3	n Lifespan Tc
LEDriving XTR \doteq H7	±20 %	14.0 mm	14.0 mm		750 hr	2000 hr
		& Regulatory Info cording Art. 33 of				
	internation ac		EO Regulation (EC) 190	7/2006	(REACh)	
Product description	Primary article identifier	•	ite list CAS No	7/2006 5. of sub	• •	Safe use instruction

Product description	Declaration no. in SCIP database
LEDriving XTR \doteq H7	34c1b231-805b-
	4aa3-908f-
	a33d6cf02d75

Product family datasheet

Download Data

	File
	User instruction LEDriving XTR
Z	User instruction GPRS_Safety symbols instructions
1	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.Refer to www.osram.com/am-guarantee for precise conditions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.